

# JohnsonDiversey Oxofoam

## Chlorinated foam cleaner

### Description

**Oxofoam** is a general purpose, chlorinated foam cleaner designed for daily use in the food, beverage and dairy industries

### Key properties

**Oxofoam** contains a balanced blend of caustic alkali, surface active agents, sequestrant and hypochlorite. It is very effective for use on a wide range of food soils including animal and vegetable fats, blood and proteins. In addition, the presence of chlorine assists removal of organic and vegetable-based stains and helps to prevent build-up of 'protein film' deposits.

**Oxofoam** is recommended for daily cleaning applications where heavy proteinaceous and fatty soiling are found in combination, such as abattoirs, poultry processors and the fish industry. It can be used for cleaning floors, walls, cutting tables, packing fillers, conveyors and other processing equipment.

**Oxofoam** is suitable for use with a wide range of foam application equipment.

### Benefits

- Effective for removal of heavy fat and protein
- Assists stain removal
- Helps prevent build-up of protein film
- Suitable for use in hard water
- Free rinsing

### Use instructions

Use **Oxofoam** at concentrations between 2-10% v/v depending on the type and degree of soiling. For specific details please refer to individual method cards.

### Technical data


Appearance	clear pale yellow liquid
Relative Density at 20°C	1.21
pH (1% solution at 20°C)	12.7
Chemical Oxygen Demand (COD)	89 gO <sub>2</sub> /kg
Nitrogen Content (N)	1 g/kg
Phosphorous Content (P)	12 g/kg

The above data is typical of normal production and should not be taken as a specification.

### Safe handling and storage information

Store in original closed containers or (where applicable) in an approved bulk tank, away from sunlight and extreme temperatures. Keep away from acids. Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

# VF5



Diverclean™

## JohnsonDiversey Oxofoam

### Product compatibility

**Oxofoam** when applied at the recommended concentration and temperature is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on soft metals such as aluminium and galvanised materials. Always rinse surfaces thoroughly after use (within 1 hour). In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

### Test method

Reagents: 0.1N Hydrochloric or sulphuric acid  
0.1N Sodium thiosulphate  
Phenolphthalein indicator

Procedure: Add 10ml of 0.1N sodium thiosulphate to 10ml of the test solution, mix well and allow to stand for about 30 seconds, add 2-3 drops of the indicator solution and titrate with the acid to a colourless end point.

Calculation: % v/v **Oxofoam** = titre (ml) x 0.44  
% w/v **Oxofoam** = titre (ml) x 0.53  
% w/w **Oxofoam** = titre (ml) x 0.53

### Available pack sizes

Article code	Pack size
5600020	20L
5600077	200L
5600134	950L
7509880	Bulk

**JohnsonDiversey (UK)**  
Weston Favell Centre  
Northampton NN3 8PD  
Tel. 0800 525 525  
[www.johnsondiversey.com](http://www.johnsondiversey.com)